



**PARA LIGHT ELECTRONICS CO., LTD.**

11F, No.8, Jiankang Rd,Zhonghe Dist,New Taipei City 253, Taiwan

Tel: 886-2-2225-3733

Fax: 886-2-2225-4800

E-mail: [para@para.com.tw](mailto:para@para.com.tw)

<http://www.para.com.tw>

**DATA SHEET**

**PART NO.:L-C295JYJGCT-U1**

**REV: A / 2**

CUSTOMER'S APPROVAL: \_\_\_\_\_

DCC: \_\_\_\_\_


DRAWING NO.: DS-78-14-0016

DATE:2021-12-03

Page

1

### ● PACKAGE OUTLINE DIMENSIONS



#### Note:

1. All dimensions are in millimeters.
2. Tolerance is  $\pm 0.1\text{mm}$  (.004") unless otherwise noted

### ● Features

- \* Dual color, top view, wide view angle Chip LED.
- \* Package in 8mm tape on 7" diameter reels.
- \* Compatible with automatic Pick & Place equipment.
- \* Compatible with Reflow soldering and Wave soldering processes.
- \* EIA STD package.
- \* I.C. compatible.
- \* Pb free product.
- \* Moisture sensitivity level: 3

### ● Chip Materials

chip	Light Color	Dice Material	Lens Color
JY	Yellow	AlInGap	Water Clear
JG	Green	AlInGap	

### ● Absolute Maximum Ratings (Ta=25°C)

Symbol	Parameter	Rating		Unit
		Yellow	Green	
P <sub>D</sub>	Power Dissipation	75	60	mW
I <sub>PF</sub>	Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	80	60	mA
I <sub>F</sub>	Continuous Forward Current	30	30	mA
V <sub>R</sub>	Reverse Voltage	5	5	V
ESD	Electrostatic Discharge Threshold (HBM)	2000	2000	V
T <sub>opr</sub>	Operating Temperature Range	-40 ~ +85		°C
T <sub>stg</sub>	Storage Temperature Range	-40 ~ +85		°C

### ● Electro-Optical Characteristics (Ta=25°C)

SYMBOL		PARAMETER	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
V <sub>F</sub>	Yellow	Forward Voltage	I <sub>F</sub> = 20mA	1.8	1.9	2.4	V
	Green			1.8	2.0	2.4	
I <sub>V</sub>	Yellow	Luminous Intensity	I <sub>F</sub> = 20mA	45	72	180	mcd
	Green			28	45	112	
2θ <sub>1/2</sub>		Half Intensity Angle	I <sub>F</sub> = 20mA		130		deg
λ <sub>D</sub>	Yellow	Dominant Wavelength	I <sub>F</sub> = 20mA	587	590	596	nm
	Green			567	570	576	nm
Δλ	Yellow	Spectral Line Half-Width	I <sub>F</sub> = 20mA		16		nm
	Green				15		nm
I <sub>R</sub>	Yellow	Reverse Current	V <sub>R</sub> = 5V			10	μA
	Green						

### Notes:

1. Luminous intensity is measured with a light sensor and filter combination that proximities the CIE eye-response curve.
2.  $\theta_{1/2}$  is the off-axis angle at which the luminous intensity is half the axial luminous intensity.
3. The dominant wavelength  $\lambda_d$  is derived from the CIE chromaticity diagram and represents the single wavelength which defines the color of the device.
4. Caution in ESD:  
Static Electricity and surge damages the LED. It is recommended use a wrist band or anti-electrostatic glove when handling the LED. All devices, equipment and machinery must be properly grounded.
5. Major standard testing equipment by "Instrument System" Model: CAS140B Compact Array Spectrometer and "KEITHLEY" Source Meter Model: 2400.

### ● Typical Electro-Optical Characteristics Curves




Fig.1 Yellow Relative Intensity vs. Wavelength




Fig.1 Green Relative Intensity vs. Wavelength

● **Yellow Typical Electro-Optical Characteristics Curves**

(25°C Ambient Temperature Unless Otherwise Noted)




Fig.2 Forward Current vs. Forward Voltage




Fig.3 Luminous Intensity vs. Forward Current




Fig.4 Relative Luminous Intensity vs. Forward Current




Fig.5 Luminous Intensity vs. Ambient Temperature




Fig.6 Forward Current Derating Curve




Fig.7 Relative Intensity vs. Angle

#### ● Green Typical Electro-Optical Characteristics Curves

(25°C Ambient Temperature Unless Otherwise Noted)




Fig.2 Forward Current vs. Forward Voltage




Fig.3 Luminous Intensity vs. Forward Current




Fig.4 Relative Luminous Intensity vs. Forward Current




Fig.5 Luminous Intensity vs. Ambient Temperature




Fig.6 Forward Current Derating Curve




Fig.7 Relative Intensity vs. Angle

### ● Label Explanation



ITEM CODE:PARRA LIGHT

PART NO:L-C295JYJGCT-U1

IV --- Luminous Intensity Code

LOT NO: EM S L 12 09 0110  
A B C D E F

A---EM: Emos Code

B---S:SMD

L---Local

D---Year

E---Month

F---SPEC.

PACKING QUANTITY OF BAG :

3000pcs for 150、170、110、155、115 series

4000pcs for 191 series


5000pcs for 192 series

DATE CODE: 2012 09 10  
G H I

G--- Year

H--- Month


I --- Day

**● Reel Dimensions**

**Notes:**

1. Taping Quantity: 4000pcs
2. The tolerances unless mentioned is  $\pm 0.1\text{mm}$ , Angle  $\pm 0.5^\circ$  , Unit: mm.



## ● Package Dimensions Of Tape And Reel




Notes: All dimensions are in millimeters.


### ● Cleaning

- \* If cleaning is required , use the following solutions for less than 1 minute and less than 40°C.
- \* Appropriate chemicals: Ethyl alcohol and isopropyl alcohol.
- \* Effect of ultrasonic cleaning on the LED resin body differs depending on such factors as the oscillator output, size of PCB and LED mounting method. The use of ultrasonic cleaning should be enforced at proper output after confirming there is no problem.


### ● Suggest Soldering Pad Dimensions



● Suggest Sn/Pb IR Reflow Soldering Profile Condition:



● Suggest Pb-Free IR Reflow Soldering Profile Condition:



### ● Bin Code List

Luminous Intensity (IV), Unit: mcd@20mA					
Yellow			Green		
Bin Code	Min	Max	Bin Code	Min	Max
P	45	71	N	28	45
Q	71	112	P	45	71
R	112	180	Q	71	112

Tolerance of each bin are  $\pm 15\%$

Dominant Wavelength (Hue), Unit: nm@20mA					
Yellow			Green		
Bin Code	Min	Max	Bin Code	Min	Max
YA	587	590	GA	567	570
YB	590	593	GB	570	573
YC	593	596	GC	573	576

Tolerance of each bin are  $\pm 1\text{nm}$

## ● CAUTIONS

### 1.Application Limitation:

The LED's described here are intended to be used for ordinary electronic equipment (such as office equipment, communication equipment and household application). Consult PARA's sales in advance for information on application in which exceptional quality and reliability are required, particularly when the failure or malfunction of the LED's may directly jeopardize life or health (such as airplanes, automobiles, traffic control equipment, life support system and safety devices).

### 2.Storage:

Do not open moisture proof bag before the products are ready to use.

Before opening the package: The LEDs should be kept at 30°C or less and 90%RH or less.

If the moisture absorbent material (silica gel) has faded away or the LEDs have exceeded the storage time, baking treatment should be performed using the following conditions.

Baking treatment: 60±5°C for 24 hours

### 3.Soldering

Do not apply any stress to the lead frame during soldering while the LED is at high temperature.

Recommended soldering condition.

Reflow Soldering:

Pre-heat 120~150 °C, 120sec. MAX., Peak temperature : 240 °C Max. Soldering time: 10 sec Max.

Soldering Iron: (Not recommended)

Temperature 300 °C Max., Soldering time : 3 sec. Max.(one time only), power dissipation of iron : 20W Max. use SN60 solder of solder with silver content and don't to touch LED lens when soldering.

Wave soldering:

Pre-heat 100 °C Max, Pre-heat time 60 sec. Max, Solder wave 260 °C Max, Soldering time 5 sec. Max. preformed consecutively cooling process is required between 1st and 2nd soldering processes.

### 4. Lead-Free Soldering

For Reflow Soldering:

- 1、 Pre-Heat Temp:150-180°C,120sec.Max.
- 2、 Soldering Temp: Temperature Of Soldering Pot Over 230°C,40sec.Max.
- 3、 Peak Temperature:260°C , 5sec.
- 4、 Reflow Repetition:3 Times Max.
- 5、 Suggest Solder Paste Formula 93.3 Sn/3.1 Ag/3.1 Bi /0.5 Cu

For Soldering Iron (Not Recommended):


- 1、 Iron Tip Temp:350°C Max.
- 2、 Soldering Iron:30w Max.
- 3、 Soldering Time:3 Sec. Max. One Time.

For Dip Soldering:


- 1、 Pre-Heat Temp:150°C Max. 120 Sec. Max.
- 2、 Bath Temp:265°C Max.
- 3、 Dip Time:5 Sec. Max.

### 5. Drive Method

Circuit model A



Circuit model B



(A)Recommended circuit.

(B)The difference of brightness between LED`s could be found due to the Vf-If characteristics of LED.