

### PARA LIGHT ELECTRONICS CO., LTD.

11F., No. 8, Jiankang Rd., Zhonghe Dist., New Taipei City 235, Taiwan,Tel: 886-2-2225-3733Fax: 886-2-2225-4800E-mail: para@para.com.twhttp://www.para.com.tw

# DATA SHEET

# PART NO.: LC292JGCT-5A-U1

REV: <u>A / 0</u>

CUSTOMER'S APPROVAL : \_\_\_\_\_ DRAWING NO. : DS-83-23-0003G

DATE : 2023-7-05

DCC : \_

Page

LD-R/E020

1



Part No. : LC292JGCT-5A-U1

REV:A/0

### • PACKAGE OUTLINE DIMENSIONS

BACK VIEW





TOP VIEW





SIDE VIEW

#### Notes:

1. All dimensions are in millimeters.

2. Tolerance is  $\pm$  0.15mm (.006") unless otherwise noted.

#### • Features

- \* Extra thin 0.4mm, Top view, Wide view angle
- \* Package in 8mm tape on 7" diameter reels.
- \* Compatible with automatic Pick & Place equipment.
- \* Compatible with Infrared and Wave soldering reflow solder processes.
- \* EIA STD package.
- \* I.C. compatible, low current application
- \* Pb free product and acceptable lead-free process
- \* Meet RoHS Green Product.
- \* Moisture sensitivity level: 3

#### DRAWING NO. : DS-83-23-0003G

#### DATE : 2023-7-05 PAGE 2 of 12

PARA-FOR-068



Part No. : LC292JGCT-5A-U1

REV:A/0

### • Chip Materials

- \* Dice Material : AlInGaP
- \* Light Color : Yellow Green
- \* Lens Color : Water Clear

### • Absolute Maximum Ratings(Ta=25°C)

Symbol	Parameter	Rating	Unit
PD	Power Dissipation	48	mW
Ipf	Peak Forward Current	60	mA
	(1/10 Duty Cycle, 0.1ms Pulse Width)		
IF	Continuous Forward Current	20	mA
VR	Reverse Voltage	5	V
ESD	Electrostatic Discharge Threshold(HBM) <sup>Note A</sup>	2000	V
Topr	Operating Temperature Range	-40 ~ +85	°C
Tstg	Storage Temperature Range	-40 ~ +85	°C

Note A :

HBM : Human Body Model. Seller gives no other assurances regarding the ability of to withstand ESD.

### • Electro-Optical Characteristics(Ta=25°C, Condition B)

Parameter	Symbol	Min.	Тур.	Max.	Unit	Test Condition
Luminous Intensity	IV	4.5		71	mcd	IF=5mA
Viewing Angle	2 <sup>θ</sup> 1/2		120		deg	Note 2
Dominant Wavelength	$\lambda d$	567		575	nm	IF=5mA
Spectral Line			15			IE-5m A
Half-Width	$\Delta \Lambda$		15		11111	IF–JIIIA
Forward Voltage	VF	1.7		2.4	V	IF =5mA
Reverse Current	IR			10	μA	VR = 5V

DRAWING NO. : DS-83-23-0003G

DATE : 2023-7-05 PAGE 3 of 12



### Part No. : LC292JGCT-5A-U1

REV:A/0

### • Bin Code List

Luminous Intensity(IV), Unit:mcd@5mA			Forward Voltage(VF), Unit:V@5mA		
Bin Code	Min	Max	Bin Code	Min	Max
J	4.5	7.1	2	1.7	1.8
K	7.1	11.2	3	1.8	1.9
L	11.2	18.0	4	1.9	2.0
М	18.0	28.0	5	2.0	2.1
Ν	28.0	45.0	6	2.1	2.2
Р	45.0	71.0	7	2.2	2.3
			8	2.3	2.4

Tolerance of each bin are  $\pm 15\%$ 

Tolerance of each bin are  $\pm 0.1$  Volt

Dominant Wavelength (Hue), Unit: nm@5mA				
Bin Code	Min	Max		
GA	567	570		
GB	570	573		
GC	573	575		

Tolerance of each bin are  $\pm 1$ nm

Notes:

- 1. Luminous intensity is measured with a light sensor and filter combination that proximities the CIE eye-response curve.
- 2.  $\theta$  1/2 is the off-axis angle at which the luminous intensity is half the axial luminous intensity.
- 3. The dominant wavelength  $\lambda$  d is derived from the CIE chromaticity diagram and represents the single wavelength which defines the color of the device.
- 4. Caution in ESD :

Static Electricity and surge damages the LED. It is recommended use a wrist band or anti-electrostatic glove when handling the LED. All devices, equipment and machinery must be properly grounded.

5. Major standard testing equipment by "Instrument System" Model : CAS140D Compact Array Spectrometer and "KEITHLEY" Source Meter Model : 2400.

DRAWING NO. : DS-83-23-0003G



Part No.: LC292JGCT-5A-U1

REV:A/0

### • Typical Electro-Optical Characteristics Curves

(25°C Ambient Temperature Unless Otherwise Noted)



Fig.2 Forward Current vs.Forward Voltage



Fig.4 Relative Luminous Intensity vs.Forward Current





Fig.3 Luminous Intensity vs.Forward Current



Fig.5 Luminous Intensity vs.Ambient Temperature



Fig.7 Relative Intensity vs.Angle

DRAWING NO. : DS-83-23-0003G

DATE : 2023-7-05 PAGE 5 of 12

PARA-FOR-068



Part No.: LC292JGCT-5A-U1

REV:A/0

#### • Label Explanation



PART NO: LC292JGCT-5A-U1 IV --- Luminous Intensity Code LOT NO: EM S L 12 09 0110 в F А C D Е A---EM: Emos Code B---S:SMD L---Local D----Year E---Month F---SPEC. PACKING QUANTITY OF BAG: 3000pcs for 150, 170, 110, 155, 115 series 4000pcs for 191 series 5000pcs for 192, 292 series DATE CODE: <u>2012</u> <u>09</u> <u>10</u> Ι G Η G---- Year H--- Month I --- Day

DRAWING NO. : DS-83-23-0003G

DATE: 2023-7-05 PAGE 6 of 12







Part No. : LC292JGCT-5A-U1

REV:A/0

### • Cleaning

- \* If cleaning is required , use the following solutions for less than 1 minute and less than  $40^{\circ}$ C.
- \* Appropriate chemicals: Ethyl alcohol and isopropyl alcohol.
- Effect of ultrasonic cleaning on the LED resin body differs depending on such factors as the oscillator output, size of PCB and LED mounting method. The use of ultrasonic cleaning should be enforced at proper output after confirming there is no problem.

Suggest Soldering Pad Dimensions(dimensions are in millimeters)



#### DRAWING NO. : DS-83-23-0003G

DATE : 2023-7-05 PAGE 9 of 12



PARA-FOR-068



### Part No. : LC292JGCT-5A-U1

REV:A / 0

### • CAUTIONS

1. Application limitation :

The LED's described here are intended to be used for ordinary electronic equipment (such as office equipment, communication equipment and household application).Consult PARA's sales in advance for information on application in which exceptional quality and reliability are required, particularly when the failure or malfunction of the LED's may directly jeopardize life or health (such as airplanes, automobiles, traffic control equipment, life support system and safety devices).

#### 2.Storage :

Do not open moisture proof bag before the products are ready to use.

Before opening the package: The LEDs should be kept at  $30^{\circ}$ C or less and 90%RH or less.

If the moisture absorbent material (silica gel) has faded away or the LEDs have exceeded the storage time, baking treatment should be performed using the following conditions.

Baking treatment:  $60\pm5$  °C for 24 hours

#### 3.Soldering

Do not apply any stress to the lead frame during soldering while the LED is at high temperature. Recommended soldering condition.

Reflow Soldering :

Pre-heat 120~150 °C, 120sec. MAX., Peak temperature : 240 °C Max. Soldering time : 10 sec Max. Soldering Iron : (Not recommended)

Temperature 300  $^{\circ}$  C Max., Soldering time : 3 sec. Max.(one time only), power dissipation of iron : 20W Max. use SN60 solder of solder with silver content and don't to touch LED lens when soldering. Wave soldering :

Pre-heat 100 °C Max, Pre-heat time 60 sec. Max, Solder wave 260 °C Max, Soldering time 5 sec. Max. preformed consecutively cooling process is required between  $1^{st}$  and  $2^{nd}$  soldering processes.

DRAWING NO. : DS-83-23-0003G

#### DATE : 2023-7-05 PAGE 11 of 12



Part No. : LC292JGCT-5A-U1

REV:A/0

#### 4. Lead-Free Soldering

For Reflow Soldering :

- 1、 Pre-Heat Temp:150-180°C,120sec.Max.
- 2. Soldering Temp:Temperature Of Soldering Pot Over 230°C,40sec.Max.
- 3、Peak Temperature:260°C, 5sec.
- 4. Reflow Repetition:2 Times Max.
- 5. Suggest Solder Paste Formula 93.3 Sn/3.1 Ag/3.1 Bi /0.5 Cu

For Soldering Iron (Not Recommended) :

- 1、 Iron Tip Temp:350°C Max.
- 2、Soldering Iron:30w Max.
- 3. Soldering Time: 3 Sec. Max. One Time.

For Dip Soldering :

- 1、Pre-Heat Temp:150°C Max. 120 Sec. Max.
- 2. Bath Temp:265°C Max.
- 3、 Dip Time:5 Sec. Max.
- 5. Drive Method



(A)Recommended circuit.

(B)The difference of brightness between LED's could be found due to the Vf-If characteristics of LED.

#### DRAWING NO. : DS-83-23-0003G

#### DATE : 2023-7-05 PAGE 12 of 12